

**Product name:** Tripropylene Glycol Regular Grade

**Issue Date:** 04/14/2017

**Print Date:** 05/25/2017

Sadara Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. PRODUCT AND COMPANY IDENTIFICATION

---

**Product name:** Tripropylene Glycol Regular Grade

**Recommended use of the chemical and restrictions on use**

**Identified uses:** Component(s) for the manufacture of urethane polymers. For industrial use.

**COMPANY IDENTIFICATION**

SADARA CHEMICAL COMPANY  
P.O. BOX 11811  
JUBAIL INDUSTRIAL CITY 31961  
KINGDOM OF SAUDI ARABIA

**Customer Information Number:**

+966 13 345 8888

**Fax:**

cig@sadara.com

+966 13 868 8097

**EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact:** +966 13 345 7222

**Local Emergency Contact:** +966 13 345 7222

---

## 2. HAZARDS IDENTIFICATION

---

**Hazard classification**

Not classified as hazardous according to regulatory criteria.

**Other hazards**

No data available

---

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

This product is a substance.

CASRN / EC-No. / Index-No.	Concentration	Component	Classification
<b>CASRN</b> 9082-00-2 <b>EC-No.</b> Not applicable <b>Index-No.</b> -	>= 20.0 - <= 40.0 %	Glycerol, propylene oxide, ethylene oxide polymer	Not classified
<b>CASRN</b> 56449-05-9 <b>EC-No.</b> 500-132-3 <b>Index-No.</b> -	>= 60.0 - <= 80.0 %	Sorbitol, propylene oxide, ethylene oxide polymer	Not classified

---

#### 4. FIRST AID MEASURES

---

##### Description of first aid measures

**General advice:** If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

**Skin contact:** Wash off with plenty of water.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

##### Indication of any immediate medical attention and special treatment needed

**Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

---

#### 5. FIREFIGHTING MEASURES

---

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**Unsuitable extinguishing media:** Do not use direct water stream. May spread fire.

##### Special hazards arising from the substance or mixture

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

**Advice for firefighters**

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions, protective equipment and emergency procedures:** Isolate area. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause a slipping hazard. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Contain spilled material if possible. Absorb with materials such as: Dirt. Sand. Sawdust. Collect in suitable and properly labeled containers. Wash the spill site with water. See Section 13, Disposal Considerations, for additional information.

---

## **7. HANDLING AND STORAGE**

---

**Precautions for safe handling:** Wash thoroughly after handling. Keep container closed. This material is hygroscopic in nature. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

**Conditions for safe storage:** Protect from atmospheric moisture. Store in a dry place. Avoid prolonged exposure to heat and air. Store in the following material(s): Carbon steel. Stainless steel.

Polypropylene. Polyethylene-lined container. Teflon. Glass-lined container. Aluminum. Plaste 3066 lined container. Plaste 3070 lined container. 316 stainless steel. See Section 10 for more specific information.

<b>Storage stability:</b>	<b>Storage Period:</b>
<b>Storage temperature:</b> 15 - 35 °C	24 Month

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Control parameters

Exposure limits are listed below, if they exist.

Exposure limits have not been established for those substances listed in the composition, if any have been disclosed.

### Exposure controls

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

### Individual protection measures

**Eye/face protection:** Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

#### Skin protection

**Hand protection:** Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Wear clean, body-covering clothing.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

Use the following CE approved air-purifying respirator: Organic vapor cartridge, type A (boiling point >65 °C)

**See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.**

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**Appearance**

Physical state	liquid
Color	clear
Odor	odourless
Odor Threshold	No test data available
pH	Not applicable
Melting point/range	Not applicable
Freezing point	No test data available
Boiling point (760 mmHg)	<i>Estimated.</i> Decomposes before boiling
Flash point	<b>closed cup</b> $\geq 200$ °C <i>ASTM D 93</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not Applicable
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	Negligible
Relative Vapor Density (air = 1)	$>1$ <i>Estimated.</i>
Relative Density (water = 1)	1.02 at 25 °C / 25 °C <i>Literature</i>
Water solubility	at 25 °C Negligible
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Kinematic Viscosity	1000 - 1300 cSt at 25 °C <i>ASTM D 445</i>
Explosive properties	Not explosive
Oxidizing properties	No
Liquid Density	1.02 g/cm <sup>3</sup> at 25 °C <i>Literature</i>
Molecular weight	No test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** No data available

**Chemical stability:** Stable under recommended storage conditions. See Storage, Section 7.

**Possibility of hazardous reactions:** Polymerization will not occur.

**Conditions to avoid:** Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

**Incompatible materials:** Avoid contact with oxidizing materials. Avoid contact with: Strong acids. Strong bases. Avoid unintended contact with isocyanates. The reaction of polyols and isocyanates generates heat.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon dioxide. Aldehydes. Alcohols. Ethers. Hydrocarbons. Ketones. Polymer fragments.

---

## **11. TOXICOLOGICAL INFORMATION**

---

Toxicological information appears in this section when such data is available.

### **Acute toxicity**

#### **Acute oral toxicity**

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Typical for this family of materials.

LD50. Rat. > 2.000 mg/kg Estimated. No deaths occurred at this concentration.

#### **Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Typical for this family of materials.

LD50. Rabbit. > 2.000 mg/kg No deaths occurred at this concentration.

#### **Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility. Vapor from heated material may cause respiratory irritation and other effects.

The LC50 has not been determined.

### **Skin corrosion/irritation**

Brief contact is essentially nonirritating to skin.

### **Serious eye damage/eye irritation**

Essentially nonirritating to eyes.

### **Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

### **Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

### **Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

### **Carcinogenicity**

Available data suggest that the material is unlikely to cause cancer.

**Teratogenicity**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

**Reproductive toxicity**

In animal studies, a similar material has been shown not to interfere with reproduction.

**Mutagenicity**

For this family of materials: In vitro genetic toxicity studies were negative.

**Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

**COMPONENTS INFLUENCING TOXICOLOGY:**

**Glycerol, propylene oxide, ethylene oxide polymer**

**Acute inhalation toxicity**

The LC50 has not been determined.

---

---

**12. ECOLOGICAL INFORMATION**

---

Ecotoxicological information appears in this section when such data is available.

**Toxicity**

**Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50. Leuciscus idus (Golden orfe). semi-static test. 96 Hour. > 1.000 mg/l. OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EC50. copepod Acartia tonsa. static test. 48 Hour. > 1.000 mg/l. Other guidelines

**Acute toxicity to algae/aquatic plants**

EC50. Desmodesmus subspicatus (green algae). static test. 72 Hour. Growth rate inhibition. > 100 mg/l. OECD Test Guideline 201 or Equivalent

EC50. Skeletonema costatum (marine diatom). static test. 72 Hour. Growth rate inhibition. > 1.000 mg/l. OECD Test Guideline 201 or Equivalent

**Toxicity to bacteria**

EC50. activated sludge. static test. 3 Hour. Respiration rates.. > 10.000 mg/l. OECD 209 Test

**Chronic aquatic toxicity**

**Chronic toxicity to aquatic invertebrates**

NOEC. Daphnia magna (Water flea). semi-static test. 21 d. mortality. >= 10 mg/l

LOEC. Daphnia magna (Water flea). semi-static test. 21 d. mortality. > 10 mg/l

**Persistence and degradability**

**Biodegradability:** Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable

**Biodegradation:** < 60 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301D or Equivalent

**Bioaccumulative potential**

**Bioaccumulation:** For this family of materials: No bioconcentration is expected because of the relatively high water solubility.

**Mobility in soil**

No data available.

**Results of PBT and vPvB assessment**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**Other adverse effects**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

---

---

**13. DISPOSAL CONSIDERATIONS**

---

**Disposal methods:**

Any disposal practice must be in compliance with all local and national laws and regulations. Do not dump into any sewers, on the ground, or into any body of water.

---

---

**14. TRANSPORT INFORMATION**

---

**Classification for ROAD and Rail transport:**

Not regulated for transport

**Classification for SEA transport (IMO-IMDG):**

Not regulated for transport

**Transport in bulk  
according to Annex I or II  
of MARPOL 73/78 and the  
IBC or IGC Code**

Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.



---

---

## **15. REGULATORY INFORMATION**

---

### **Label**

Classification and labeling have been performed according to regulations.

### **Hazard symbol and Indication of danger**

Not classified as hazardous according to regulatory criteria.

---

---

## **16. OTHER INFORMATION**

---

### **Product Literature**

Additional information on this product may be obtained by calling your sales or customer service contact.

### **Revision**

Identification Number: 3226 / S100 / Issue Date: 04/14/2017 / Version: 1.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal reference within our company.

Sadara Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.